

DIGITAL PODIUM



OS-MP-401



Podium Features

Used in University, Middle/ High Schools, Meeting Room, Auditorium, Polytechnic High Tech Rooms, Smart Classroom

- Ergonomically designed interface, expert quality, powder coated steel body.
- Easy moving wheels / caster with locks.
- The effective lesson through wire/ wireless microphones **(optional)**.
- High quality gooseneck microphone (low howling noise) **(optional)**.
- Control all multimedia devices in classroom by the convenient integrated controller **(optional)**.
- The super structure composite with 19" / 21.5" LED tablet monitor.
- Pneumatic lifting tablet monitor.
- Touch pen **(optional)**.
- Movable keyboard tray with locks.
- Central control panel for switching all inputs **(optional)**.
- Storage drawer for visualizer.
- Laptop interface / ports **(optional)**.
- CD / DVD Drive (optional) (main frame in the cabinet).
- High Power Amplifier and speakers **(optional)**.
- Central Locking - RFID / Bio Metric access(optional) for secure access to the system.
- 120mm sized cooling fan for device temperature control.
- International Standard equipment rack.
- Annotation software, white board, Screen Capturing Session recording and export to PDF.
- Podium Dimension- Front Height 44" / Height from Presenter side 42" / Top depth 28" / Top width of 26"

SPECIFICATIONS

Model	OS-MP-401
Type/Mounting	Free Standing
Construction	The Lectern is wheel mounting capable of moving in all direction with facility of locks. The Enclosure made of 1.6 mm thick CRCA polymer powder coated, design to work in harsh environmental conditions and vandal resistant
Touch Display	21.5" Touch projected Capacitive p-cap Colour LCD Touch monitor, Antiglare Resolution 1280 X 1024/1920 X 1080 Brightness 250 nits Active Matrix Color TFT Scratch resistant when used with Electronic Pen / Stylus Built in highly sensitive interactive panel with TILT functionality
Electronic Pen	Electronic pen with 2 buttons for better editing Active Touch pen
Enclosure Ports	USB 3.0*2, VGA IN/ HDMI IN/ DVI ports, Power socket
Cooling	1 / 2 Fans (optional)
Power Management	Screen Blanking, Setup Password, Power supply SMPS Surge protected
ENVIRONMENTAL	
EMC & Safety	FCC Class B for EMC and CE Marking (for CPU and Display)
Temp. & Humidity	Operating Ambient temperatures - So C to 400 C Storage Temperature - (-)100 C to 550 C Operating Humidity - 400 at 90% RH non-condensing Storage Humidity - 400 at 90% RH non-condensing
Annotation Software	Includes features like draw, choose pens, annotate, erase, color, shape, size, text, edit, font, stamp, move, capture picture, video, save, rotate, undo, image gallery, print, floating keyboard and background
Console Panel Ports	1 X RGB Input (other than input of PC in the Lectern to facilitate extra PC/Laptop/ Visualizer. USB Port from the panel to facilitate inputs directly from the pen drive/USB based Hard disk drive. RJ45 LAN port at the panel to connect network. Selection switches to toggle between various sources for the output on the projection screen.
Built-in Device	On the panel with easy access and control consisting of. Audio Visual Switch with 4 input ports (RGB / HDMI / DVI / RCA) and 2 Output ports for selection of source. (optional)
PROVISION FOR ADDITIONAL DEVICE	
	Sliding tray for LAPTOP/ NOTEBOOK / TABLET Sliding Shelf for Input device / visual presenter/ books I documents Space for Keyboard and Mouse
Security	Built-In optional RFID authentication system or Bio metric for secure access to system (Central Locking) (optional)
Warranty	12 months