

SOFT-VC CODEC



Ordain Core enables vast web conferencing platform support including one-click Skype for Business and Zoom meeting launch, wireless document sharing, web browsing, and access to content from network drives, The start screen has everything a user needs when they walk into the meeting room.

- Wide Support for Web Conferencing Platforms, including Zoom, Microsoft Teams, WebEx etc.
- Users can quickly and easily join a scheduled or Zoom meeting without having to find a link or meeting invite, enhancing productivity by reducing wait time.
- Wireless Sharing – Ordain Core supports Airplay and Google Cast so users can easily share content from mobile devices or PC.
- Built-in Document Viewers – Users can present content without bringing any devices to the room. Users simply walk into the room, start a session, navigate to their document (USB drive, network drive, or the web), and start their presentation.
- 4K, Dual Monitor and Touch Screen Support – Ensure meeting spaces are as engaging as they are simple to use.
- Network Drive Support – Many enterprises choose to have all their documents stored on network drives. If a user authenticates into a meeting, they will have access to content stored on those drives. As Core is always on, there is no waiting for boot up time allowing users to access their network content quickly enhancing workforce productivity.



Specification

Model	OS-SVC2121
Processor	Intel®
SOC	Intel® Core™ i3/i5/i7
Memory	4 GB DDR4 up to 32 GB
Performance	2 M Cache, up to 4,20 GHz ±
Storage	256GB/512GB/1TB SSD
Graphics	Intel® UHD Graphics
Wireless	2.4Ghz /5Ghz /BT 4.2
WIFI/BT	802.11ac / BT 4.2
Lan	10/100/1000 Gigabit LAN
Audio	AUDIO IN + OUT
Interfaces	USB-A 3.0 x 4 USB-A 2.0 x 2 RJ45 10/100/1000 M x 1 HDMI 1.4 out (4K@30 Hz) x 1 Jack 3,5 mm Line out x 1 Jack 3,5 mm Mic in x 1 WIFI/BT ANT x 2 Power button x 1 Power LED x 1 SSD LED x 1
Operating System	Windows / Linux
Power Input	12-19 V DC IN
TPM	TPM 2.0
Watchdog	Support
Material	Metal
Dimensions	180 × 119 × 30 mm
Temperature	Operating 5°C~45°C Storage -10°C~50°C
Relative Humidity	5%~95% (non-condensing))
Net Weight	1 Kg
DISPLAY PORT	DP / HDMI